



TacTiles Technical Data Sheet

Chemical Composition:

Compounded acrylic adhesive, applied to PET polyester backing with PET polyester release liner.

Appearance:

Clear 7.5cm * 7.5cm polyester squares with colored print, supplied on white polyester release liner. Available in rolls of 500.

Product Specifications:

Solids (%) Greater than 99 %. Dimensions 7.5cm * 7.5cm

Product Description/Applications:

TacTiles replace adhesives when used to install Interface Commercial modular carpet with GlasBac® and GlasBac RE backings, only. TacTiles have an exceptionally low odour and “zero” calculated VOC’s, which make them ideal for use in schools, healthcare facilities, public and private buildings and any place where odour is a concern. TacTiles use a small quantity of a pressure sensitive adhesive, applied on one side of a polyester film, to connect Interface Commercial carpet modules together to form a stable surface over almost any hard surface.

Surface preparation requirements for installations with TacTiles are the same as those for installations where adhesives would be used.

TacTiles are not to be used for installing InterfaceFLOR Commercial modular carpet onto stairs, or over existing carpet surfaces. The flammability performance of InterfaceFLOR Commercial modular carpet remains the same when TacTiles are used in place of adhesives. The adhesive used on TacTiles resists water and alkaline solutions, and resists plasticizer migration.

Storage Conditions:

TacTiles are generally resistant to both moisture and temperature. TacTiles that become wet should be allowed to air-dry before being used.

Product Installation:

Please refer to the TacTiles Installation Instructions for full details. Installation Instructions are available at <http://www.interfaceNZ.com> – *Documents and Warranties*

